

Patriot 500 Spraysafe System

Material Flow Rate: 3 gallons per minute (without tip)

20oz. CO2 Bottle will Pump: 10 gallons (approx.)

Material Handling: Directly from the container

Maximum PSI: 70 psi / Maximum tip pressure

Viton Pumps support the following materials: Oils, Solvents and Hydrocarbons such as, Curing Compounds, Form Release Agents, Form Oil, Diesel, Xylene-based Sealers and Water Based Sealers. **DO NOT USE:** Gasoline, Ketones, Acetones, Ammonia or Ethanol

EPDM Pumps support the following materials: Alcohols and Ketones such as Acetone Dye, Soaps and Water-based Sealers. **DO NOT USE:** Xylene-based sealers, Gasoline, Oils, Solvents, Soaps with Solvents or Aromatic Hydrocarbons



Model No. PAT 500-040 (EPDM)
Model No. PAT 500-020 (Viton)

Patriot System pumps can be purchased with internal seals composed of either EPDM or Viton material. All AmeriPolish and Dye-N-Seal dyes are applied using EPDM pumps. Please check the application data to ensure your pump is configured correctly for your application.

© 2010 Dynamic Diamond Tooling

Dynamic Diamond Tooling | ph: 407-298-7050 | fax: 407-298-7051
Sales@DynamicDiamondTooling.com | 2507 Silver Star Rd | Orlando, FL 32804